



I2000/K2000/N2000	Semina	Livona/LED	Topas
	Semi-cassette awning	Open awnings	
<p>I/K2000: 1-unit: 700 cm x 400 cm 2-unit: 1,200 cm x 400 cm N2000: 600 cm x 350 cm</p> <p>I/K2000: 198 mm x 211 mm N2000: 202 mm x 197 mm</p> <p>— ● as standard ○ 5° – 40° can be installed on walls, ceilings and rafters ○ LED Design/3Spot bar ●</p>	<p>700 cm x 350 cm</p> <p>204 mm x 204 mm</p> <p>— ● as standard ○ 5° – 40°</p>	<p>Livona: 1-unit: 700 cm x 400 cm Livona: 2-unit: 1,200 cm x 400 cm Livona LED: 600 cm x 400 cm MiniMax: 500 cm x 400 cm with roof: 282 mm x 190 mm without roof: 275 mm x 190 mm MiniMax with roof: 282 x 283 mm MiniMax without roof: 275 x 283 mm</p> <p>○ only without LED and Valance Plus ● as standard ○ 5° – 20° MiniMax: 5° – 15°</p> <p>● Livona LED: 2 light rings, LED Slim light bar ●</p>	<p>1-unit: 700 cm x 400 cm 2-unit: 1,200 cm x 400 cm</p> <p>with roof: 220 mm x 210 mm without roof: 210 mm x 180 mm</p> <p>— ● as standard ○ 5° – 40°</p> <p>○ LED Design/3Spot bar ●</p>
—	—	500 cm/600 cm	—
—	—	350 cm/300 cm	—
—	—	313 mm x 190 mm	—
—	—	●	—
—	—	○	—
—	—	5° – 20°	—
—	—	100 cm, 150 cm, 210 cm	—
●	●	●	●
○	○	○	○
●	●	●	●
●	●	●	●
—	—	● / ○ only Valance Plus	—
—	—	● / ○ only Valance Plus	—
—	—	● / ○ only Valance Plus	—
○	○	○	○
○	○	○	○
○	○	○	○
○	○	○	○

wind force 5 on the Beaufort scale and wind resistance class 2 according to DIN 13561