

## Cabinet Technical Data

- ♥ Dimensions Overall (HWD): 530 x 420 x 240mm (Incl. lock shroud and Beacon if fitted)
- ♥ Internal Dimensions Cabinet (HWD): 500 x 370 (310min) x 175mm
- ♥ Dimensions (Incl. Packaging): 540 x 500 x 300mm (Shipping carton)
- ♥ Cabinet weight (empty): 12.8Kg (28lbs)
- ♥ Electrical Requirements: 120-240VAC, 50-60Hz, 100W (Max)
- ♥ Electrical Safety: All electrical components concealed behind fixed cover. Full product serial numbering and labelling compliant with BS7671 regulations
- ♥ Cabinet material: Grade 304 Stainless Steel throughout
- ♥ Green paint finish: Polyester Powder Coat
- ♥ Cabinet IP rating: IP65 to BS EN 60529 as installed (end user configuration)
- ♥ Heater: 100W touch safe thermostatically controlled
- ♥ Cabinet internal light: 3W LED strip (only operates when door is open)
- ♥ External lock illumination: LED with PIR switch (active dusk to dawn only)
- ♥ Optional LED Beacon light: Integrated Green LED with dusk to dawn control
- ♥ Push button Lock: Proprietary digital electronic lock with 'low effort' push buttons and audible/visual feedback. Single/multiple Access Code options. Manual key override
- ♥ Approvals: CE, 2004/108/EC, 2006/95/EC, 2011/65/EU. HeartSafe's UK based supply chain is fully ISO9001 and ISO14001 compliant
- ♥ Supplied with full installation template, instructions, warranty, serial numbers and certification

